

Single Pole Connectors Grounding Type BMC1s Series Housing 10 Ampers

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: TLC
- Certification: CE
- Model Number: G, BMC
- Minimum Order Quantity: 500
- Price: USD
- Packaging Details: Carton
- Delivery Time: 5-30 working days
- Payment Terms: T/T
- Supply Ability: 100K pcs per month



Product Specification

- Connector Gender: Male/Female
- Material: UL94 V-0
- Current Rating: 10A
- Connector Type: Wire-to-Wire
- Cable Specification: 0.3mm²-10mm²
- Insulation Resistance: 1000MΩ
- Contact Resistance: 20mΩ
- Product Name: Battery Modular Connectors
- Highlight: **Battery Modular Connectors 10A,
Battery Modular Connectors 10 Ampers,
10A Single Pole Connectors Grounding Type**

for more products please visit us on cableslugs.com



BMC1S Series

SINGLE POLE CONNECTORS
Grounding type

Specifications	
Operating Temperature	Range -20℃ to 105℃
Flammability of Housing	UL 94 V-0
Contact Retention Force	3.8 mm
Max. Wire Insulation Force	25 Lbs
Rated Current	10 Amperes
Rated Voltage	600 Volts AC & DC
Dielectric Voltage Withstand	2200 Volts DC

Housing—10 Amperes

Material
Housing: polycarbonate

ITEM NO.	RATED CURRENT	TYPE	COLOR	DIMENSION(mm)(inch)			Q'TY BOX
				H	W	L1	
G1327-MG	10 Amperes	Pin	Green	8.4 (.320)	8.4 (.320)	48.0 (1.890)	500
G1327-FG	10 Amperes	Socket		8.4 (.320)	8.4 (.320)	48.0 (1.890)	500

Contact—10 Amperes

Material
Contact: Brass
Plating: Tin


ITEM NO.	RATED CURRENT	TYPE	WIRE RANGE mm (A.W.G.)	DIMENSION(mm)(inch)				Q'TY BOX (ROLL)
				H	W	L1	L2	
S1332-MG2ST	10 Amperes	Pin	1.5-2.5 (16-14)	22.4 (.882)	3.3 (.130)	2.4 (.094)	16.1 (.634)	4,000
S1331-FG2ST	10 Amperes	Socket	1.5-2.5 (16-14)	22.4 (.882)	3.3 (.130)	2.8 (.110)	16.5 (.650)	4,000



ACCESSORIES - PCB CONNECTORS


Contact — 25 Amperes

Material
Contact: Copper
Plating: Tin



ITEM NO.	RATED CURRENT	DIMENSION mm (inch)					Q'TY BOX
		L	W	B	H	T	
R1377G1	25 Amperes	25.0(.984)	3.6(.142)	1.3(.051)	11.0(.433)	0.8(.031)	1,000
R1377G2	25 Amperes	25.8(1.016)	3.6(.142)	1.3(.051)	18.9(.744)	0.8(.031)	1,000
R1317G1	25 Amperes	28.8(1.134)	1.3(.051)	3.6(.142)	18.9(.744)	0.8(.031)	1,000

Operating sequence view



TLC TERMINALS INC.
Battery Modular Connectors

199

Product Description:

Introducing our top-quality Battery Modular Connectors

At RS Connectors, we are proud to offer high-grade Battery Modular Connectors, designed to meet the needs of a variety of industries. We understand the importance of reliable and efficient connectivity for battery systems, which is why our products are guaranteed to meet all of your requirements.

As a leading supplier in the market, we strive to provide our customers with outstanding products of the highest quality. Our connectors feature outstanding precision and sophisticated mechanism, ensuring perfect installation and reliable performance even in the most demanding conditions.

We are committed to providing our customers with safe and dependable connectors that match their performance needs and expectations - and our Battery Modular Connectors are no exception. Enhanced with safety features, our connectors guarantee fast, reliable, and safe connection in any situation.

Features:

At our company, we take pride in offering high-quality products. Our Battery Modular Connectors are no exception. Using premium materials, we guarantee that these connectors are more durable and can guarantee long-lasting performance.

Furthermore, we ensure that each connector is made with precise engineering and strict quality control measures. These features work together to provide a secure and stable connection, minimizing the risk of power loss or interruptions.

You can trust that our Battery Modular Connectors will serve as reliable power sources to you.

Technical Parameters:

Attributes	Specifications
------------	----------------

Connector Gender	Male/Female
Terminal Type	Crimp/Solder
Connector Type	Wire-to-Wire
Application	Battery
Material	PA66+GF
Connector Style	Modular
Insulation Resistance	1000MΩ
Current Rating	2A-50A
Cable Specification	0.3mm2-10mm2
Contact Resistance	20mΩ
Series	BMC1 SERIES

Applications:

In an ever-changing world, versatility is key. That is why we have designed our connectors to be modular - to easily adapt and customize to any application you are using.

For battery-powered equipment, our connectors are especially suited to your needs. From electric vehicles to renewable energy systems, our connectors are flexible and easily customized to meet your needs.

With its reliable performance and ability to adapt to various electrical systems, our connectors provide you a more cohesive solution to any project.

Customization:

Battery Modular Connectors by TLC

Product Information:

Brand Name: TLC

Model Number: G, BMC

Place of Origin: China

Certification: CE

Minimum Order Quantity: 500

Price: USD

Packaging Details: Carton

Delivery Time: 5-30 working days

Payment Terms: T/T

Supply Ability: 100K pcs per month

Contact Resistance: 20mΩ

Connector Style: Modular

Cable Specification: 0.3mm2-10mm2

Material: PA66+GF

Connector Gender: Male/Female

TLC's Battery Modular Connectors (BMC1 SERIES) are perfect for your applications. With a minimum order quantity of 500, you get the best price at USD per piece. Our connectors are made of PA66+GF and feature a contact resistance of 20mΩ. We offer a variety of cable specifications, from 0.3mm2-10mm2. We provide packaging in carton and delivery within 5-30 working days. Payment terms are T/T and our supply ability is 100K pcs per month.

Support and Services:

Battery Modular Connectors Technical Support and Services

The technical support and services for Battery Modular Connectors are available and provided by our experienced team of engineers and technicians. Our team is ready to assist you with any questions or concerns you may have regarding the installation, maintenance and operation of your product.

Our technical support and services include:

Troubleshooting and diagnostic support

Installation and configuration assistance

Product customization

Software and hardware updates

Product maintenance and repair

24/7 phone support

We are committed to providing superior technical support and services for all of our products. If you have any questions or need assistance, please do not hesitate to contact us.

Packing and Shipping:

Packaging and Shipping Battery Modular Connectors

We package and ship Battery Modular Connectors in the following manner:

Connectors are placed in anti-static bags and securely taped.

The bags are then placed in a corrugated cardboard box.

The box is secured with strong tape.

The box is then labeled with the weight and shipping address.

The box is placed with other packages for shipping.

FAQ:

Q1: What is the brand name of the Battery Modular Connectors?

A1: The brand name of the Battery Modular Connectors is TLC.

Q2: What is the model number of the Battery Modular Connectors?

A2: The model number of the Battery Modular Connectors is G and BMC.

Q3: Where is the Battery Modular Connectors from?

A3: The Battery Modular Connectors are from China.

Q4: What is the certification of the Battery Modular Connectors?

A4: The Battery Modular Connectors have CE certification.

Q5: What is the minimum order quantity of the Battery Modular Connectors?

A5: The minimum order quantity of the Battery Modular Connectors is 500 pieces.



TLC TERMINALS TECHNOLOGY LIMITED



+8615338876153



joe@t-terminals.com



cableslugs.com

4B Huafeng Industrial Park Baolong 1 Road Baolong Street, Longgang District, Shenzhen City