

Standard PCB Terminals Tin Plated Pcb Screw Terminal 20-500A

Our Product Introduction

for more products please visit us on cableslugs.com

Basic Information

- Place of Origin: China
- Brand Name: TLC
- Model Number: T
- Minimum Order Quantity: 1000pcs
- Price: USD
- Packaging Details: bag, carton package
- Delivery Time: 5-30 working days
- Payment Terms: T/T
- Supply Ability: 1.5KK pcs per month



Product Specification


- Surface Treatment: Tin Plated
- Terminal Type: PCB
- Current Rating: 20-500A
- Size: Standard
- Color: Silver
- Material: Copper Alloy
- Operating Temperature: -40 ~+105
- Package: Bag
- Highlight: **Standard PCB Terminals Tin Plated 500A,
500A Pcb Screw Terminal,
Pcb Screw Terminal 20A**



Terminal Connector



T4130




技术参数 (Technical data)

间距 (Center Space)	5,0X10,1mm
额定电流 (Rated Current)	50A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4131




技术参数 (Technical data)

间距 (Center Space)	10,0X10,5mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4132




技术参数 (Technical data)

间距 (Center Space)	10,0X10,5,0mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4133




技术参数 (Technical data)

间距 (Center Space)	6,0X12,0mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4023




技术参数 (Technical data)

间距 (Center Space)	8,5X11,0mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24 lbf · in



T4134




技术参数 (Technical data)

间距 (Center Space)	10,0X10,5mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4135




技术参数 (Technical data)

间距 (Center Space)	10.0X16.5mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30bf · in



T4136




技术参数 (Technical data)

间距 (Center Space)	9.6X16.5mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30bf · in



T4137




技术参数 (Technical data)

间距 (Center Space)	10.0X16.5mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30bf · in



T4138




技术参数 (Technical data)

间距 (Center Space)	16.0X14.5mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30bf · in



T4139




技术参数 (Technical data)

间距 (Center Space)	11.7X12.5mm
额定电流 (Rated Current)	120A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30bf · in



T4140




技术参数 (Technical data)

间距 (Center Space)	10.0X10.5, 0mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24bf · in



T4141




技术参数 (Technical data)

间距(Center Space)	6.5X10.3mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14lbf · in



T6011




技术参数 (Technical data)

间距(Center Space)	6.25X13mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24lbf · in



T6012




技术参数 (Technical data)

间距(Center Space)	6.25X13mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24lbf · in



T6013




技术参数 (Technical data)

间距(Center Space)	6.25X13.0mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24lbf · in



T6014




技术参数 (Technical data)

间距(Center Space)	6.25X15.0mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in



T6015




技术参数 (Technical data)

间距(Center Space)	6.0X15.0mm
额定电流(Rated Current)	180A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24lbf · in



T6016




技术参数 (Technical data)

间距 (Center Space)	6.0X12.6mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in



T6017




技术参数 (Technical data)

间距 (Center Space)	6.25X13.0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24 lbf · in



T6003




技术参数 (Technical data)

间距 (Center Space)	6.25X13.0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in



T6018




技术参数 (Technical data)

间距 (Center Space)	6.25X13.0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in



T6019




技术参数 (Technical data)

间距 (Center Space)	6.25X13.0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in



T6020



技术参数 (Technical data)

间距 (Center Space)	6.0X9.0mm
额定电流 (Rated Current)	120A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24 lbf · in




T6021



T6022




T6006




技術參數 (Technical data)

间距(Center Space)	6.0X9.0mm
额定电流(Rated Current)	120A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24bf · in



技術參數 (Technical data)

间距(Center Space)	6.4X14.5mm
额定电流(Rated Current)	100A
压线螺钉(Screw)	M6
焊接端子(Female Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in



技術參數 (Technical data)

间距 (Center Space)	8.25X16.5mm
额定电流 (Rated Current)	80A
压接螺钉 (Screw)	M8
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in




T6004



T6005




T6023




技術參數 (Technical data)

间距(Center Space)	8.25X16.5mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M8
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in



技術參數 (Technical data)

间距(Center Space)	8.25X16.5mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M8
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in




技术参数 (Technical data)

间距(Center Space)	8.75X13.5mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30bf · in



T6024




技术参数 (Technical data)

间距 (Center Space)	8,5X13,0mm
额定电流 (Rated Current)	120A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T6025




技术参数 (Technical data)

间距 (Center Space)	8,5X13,0mm
额定电流 (Rated Current)	120A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T6026




技术参数 (Technical data)

间距 (Center Space)	10,5X13,0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in



T4601




技术参数 (Technical data)

间距 (Center Space)	5,0X7,7mm
额定电流 (Rated Current)	40A
压线螺钉 (Screw)	M3
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	6 lbf · in



T4602




技术参数 (Technical data)

间距 (Center Space)	4,0X9,0mm
额定电流 (Rated Current)	50A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T4603




技术参数 (Technical data)

间距 (Center Space)	4,0X9,0mm
额定电流 (Rated Current)	40A
压线螺钉 (Screw)	M3
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	6lbf · in



T4604




技术参数 (Technical data)

间距 (Center Space)	4,0X9,0mm
额定电流 (Rated Current)	40A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T4605




技术参数 (Technical data)

间距 (Center Space)	8,25X16,5mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M8
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in



T4606




技术参数 (Technical data)

间距 (Center Space)	6,3X9,8mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T4607




技术参数 (Technical data)

间距 (Center Space)	6,25X13,0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M6
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	30lbf · in



T4608




技术参数 (Technical data)

间距 (Center Space)	6,5X11,5mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in



T4609



技术参数 (Technical data)

间距 (Center Space)	5,5X11,0mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in




T4610



T4611




T4612




技術參數 (Technical data)

间距(Center Space)	10.5X13.0mm
额定电流(Rated Current)	80A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in



技术参数 (Technical data)

间距(Center Space)	6.5X15mm
额定电流(Rated Current)	100A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in



技術參數 (Technical data)

间距(Center Space)	5.5X11.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	30lbf · in




T4501



T4502




T4503




技术参数 (Technical data)

间距(Center Space)	5.0X8.0mm
额定电流(Rated Current)	40A
压线螺钉(Screw)	M3
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	6 lbf · in



技術參數 (Technical data)

间距(Center Space)	5.0X8.0mm
额定电流(Rated Current)	40A
压线螺钉(Screw)	M3
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	6 lbf · in




技术参数 (Technical data)

间距(Center Space)	6.0X9.0mm
额定电流(Rated Current)	50A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14bf · in



T4504




技术参数 (Technical data)

间距 (Center Space)	6.0X9.0mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T4505




技术参数 (Technical data)

间距 (Center Space)	6.4X3.6mm
额定电流 (Rated Current)	60A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14lbf · in



T4506




技术参数 (Technical data)

间距 (Center Space)	10.5X13.0mm
额定电流 (Rated Current)	80A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in



T4507




技术参数 (Technical data)

间距 (Center Space)	8.5X12.5mm
额定电流 (Rated Current)	100A
压线螺钉 (Screw)	M5
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	24lbf · in



T4401




技术参数 (Technical data)

间距 (Center Space)	5.2X8.4mm
额定电流 (Rated Current)	50A
压线螺钉 (Screw)	M3
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	6lbf · in



T4402




技术参数 (Technical data)

间距 (Center Space)	6.2mm
额定电流 (Rated Current)	40A
压线螺钉 (Screw)	M4
焊接端子 (Terminal Body)	Brass, Tin Plated
螺钉扭矩 (Screw Torque)	14 lbf · in



T4403




技术参数 (Technical data)

间距(Center Space)	4.6X9.0mm
额定电流(Rated Current)	40A
压线螺钉(Screw)	M3.5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	10lbf · in



T4404




技术参数 (Technical data)

间距(Center Space)	10.5X13.0mm
额定电流(Rated Current)	30A
压线螺钉(Screw)	M3
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	6 lbf · in



T4405




技术参数 (Technical data)

间距(Center Space)	9.0X9.3mm
额定电流(Rated Current)	50A
压线螺钉(Screw)	M5
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	24lbf · in



T4040




技术参数 (Technical data)

间距(Center Space)	9.0X13.2mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14lbf · in



T2012




技术参数 (Technical data)

间距(Center Space)	9.0mm
额定电流(Rated Current)	30A
压线螺钉(Screw)	M3
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	6 lbf · in



T-200A-06



技术参数 (Technical data)

间距(Center Space)	9.0 mm
额定电流(Rated Current)	200A
压线螺钉(Screw)	M6
焊接端子(Terminal Body)	Copper, Tin Plated
螺钉扭矩(Screw Torque)	40-60 kgf · cm

Product Description:

PCB Terminals are specially designed for reliable connections in the power industry. They are made of high-quality material and feature silver color with tin plated surface treatment. With superior corrosion resistance, they provide reliable connections in a wide temperature range, from -40 to +105. The current rating is up to 500A, making them ideal for demanding applications. Furthermore, they are available in standard sizes, so you can easily find the right one for your specific needs. Our Power Tab terminal and Terminal Pin are also perfect for soldering and provide a secure and sturdy connection in combination with the Solder Pin Connector.

Features:

Product Name: PCB Terminals
Package: Bag
Surface Treatment: Tin Plated
Current Rating: 20-500A
Material: Copper Alloy
Operating Temperature: -40 ~+105
Metal Terminal Pin
High current terminal pin
Solder Pin Connector

Technical Parameters:

Features	Specifications
Surface Treatment	Tin Plated
Package	Bag
Terminal Type	PCB
Solder Pin Connector	Power Tab terminal, High current terminal pin
Operating Temperature	-40 ~+105
Current Rating	20-500A
Material	Copper Alloy
Size	Standard
Color	Silver

Applications:

TLC's T PCB terminal pin is a metal terminal pin connector designed for soldering to your printed circuit boards (PCBs). It is made of durable copper alloy and is highly resistant to temperature fluctuations, ranging from -40 to +105. This reliable connector can handle current up to 500A. The surface is treated with tin plating for added corrosion and abrasion resistance. It comes in a convenient bag package for easy storage and transport. With its innovative design, the T PCB terminal pin is an ideal solution for a variety of applications. The T PCB terminal pin is perfect for connecting PCBs to other components, such as power supplies, transistors, and integrated circuits. Its robust construction ensures a secure connection with a long-lasting performance. Whether you are building a prototype or a large-scale production, the T PCB terminal pin is the perfect choice. Choose TLC's T PCB terminal pin for your next project. It is the perfect solution for any application requiring a reliable PCB terminal pin. With its superior performance and exceptional durability, you can be sure that your PCB connections will last for years to come.

Customization:

Customized PCB Terminals from TLC

Brand Name: TLC
Model Number: T
Place of Origin: China
Surface Treatment: Tin Plated
Size: Standard
Operating Temperature: -40 ~+105
Current Rating: 20-500A
Material: Copper Alloy

We offer customized PCB Terminals from TLC, which are specifically designed for low-voltage applications. Our metal terminal pins are made of copper alloy, and they come with tin plated surface for added durability and corrosion resistance. With a standard size, they have an operating temperature range of -40 ~+105 and a current rating of 20-500A.

Support and Services:

PCB Terminals Technical Support and Services

We provide a range of technical support and services for our PCB Terminals to ensure our customers get the most out of their product. Our services include:

- 24/7 online technical support
- Free technical seminars and webinars
- Installation and maintenance services
- Fault detection and diagnosis
- Warranty and repair services

We are committed to providing our customers with the best possible customer service and technical support. If you have any questions or concerns, please don't hesitate to contact us.

FAQ:

- ▶ Q: What is the brand name of PCB Terminals?
- ▶ Q: What is the model number of PCB Terminals?
- ▶ Q: Where is PCB Terminals made?
- ▶ Q: What are the features of PCB Terminals?
- ▶ Q: What is the application scope of PCB Terminals?



TLC TERMINALS TECHNOLOGY LIMITED



+8615338876153



joe@t-terminals.com



cableslugs.com

4B Huafeng Industrial Park Baolong 1 Road Baolong Street, Longgang District, Shenzhen City